


JIC



26791-90° JIC Female Swivel 74° Cone Seat SAE J514

Material: low or medial Carbon steel.

Surface treatment: trivalent or hexavalent chromium passivating Zinc (CR3+ or CR6+).

Inner packing: Plastic bag.

Outer packing: Standard exporting carton, seaworthy pallet.

Lutong is specialized in supply of hydraulic hose fittings with good quality and favorable price.

Technical Data

PART NUMBER	SCREW THREAD E	HOSE BORE		DIMENSIONS			
		DN	DASH	A	C	H	S2
26791-04-03	7/16°x20	5	03	26 . 5	9	30 . 5	15
26791-04-04	7/16°x20	6	04	30	9	33 . 5	15
26791-05-04	1/2°x20	6	04	30	9 . 5	34	17
26791-05-05	1/2°x20	8	05	33	9 . 5	37	17
26791-05-06	1/2°x20	10	06	35 . 5	9 . 5	39 . 3	17
26791-06-04	9/16°x18	6	04	30	10 . 5	34	19
26791-06-05	9/16°x18	8	05	33	10 . 5	37	19
26791-06-06	9/16°x18	10	06	35 . 5	10 . 5	39 . 3	19
26791-06-08	9/16°x18	12	08	41	10 . 5	45 . 5	19
26791-08-06	3/4°x16	10	08	35 . 5	11	41 . 3	24
26741-08-08	3/4°x16	12	08	41	11	47	24
26791-08-10	3/4°x16	16	10	56 . 5	13	51 . 5	24
26791-10-08	7/8°x14	12	08	41	13	48	27
26791-10-10	7/8°x14	16	10	56 . 5	13	52 . 5	27
26791-10-12	7/8°x14	20	12	67	13	64	27

26791-12-08	1 . 1/16°x12	12	08	41	15	49 . 5	32
26791-12-10	1 . 1/16°x12	16	10	56 . 5	15	54	32
26791-12-12	1 . 1/16°x12	20	12	65 . 5	15	63 . 5	32
26791-12-16	1 . 1/16°x12	25	16	76 . 7	15	70	32
26791-14-12	1 . 3/16°x12	20	12	65 . 5	15	63 . 5	36
26791-16-12	1 . 5/16°x12	20	12	65 . 5	16	63 . 5	41
26791-16-16	1 . 5/16°x12	25	16	76 . 7	16	70	41
26791-16-20	1 . 5/16°x12	32	20	91 . 5	16	81	41
26791-20-20	1 . 5/8°x12	32	20	91 . 5	17	80 . 5	50
26791-24-20	1 . 7/8°x12	32	20	91 . 5	20	79 . 5	55
26791-24-24	1 . 7/8°x12	40	24	109 . 4	20	94	55
26791-32-32	2 . 1/2°x12	50	32	133 . 1	23 . 5	121 . 8	75

Note: 1. For use with braided hoses 2 . If use with spiral hoses, hose fitting series number is 26792 -xx-xx.